

Retail Pricing
 Pricing subject to change without notice.

DvLED - All In One

Model	Description
LAA015F-CMS	130" AIO , 1.5mm , 500nit, 3 in 1 (1 of LAA015FL9B5, 8 of LAA015FL9B6, 1 of ACC-LAASF15)
LAEB015-GN	DVLED 1.56 mm pitch FHD, contrast ratio 3,000, processing depth : 16 bit, 12 x 6 72 LDM modules, Fixed wall mount frame included , Motorized Stand - Optional Purchasing Item, Standard 2 year warranty & 5% Spare part)

Commercial - TV-No Wifi

Model	Description
43UR340C9UD	43 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.
50UR340C9UD	50 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.
55UR340C9UD	55 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.
65UR340C9UD	65 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.
75UR340C9UD	75 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.
86UR340C9UD	86 UHD HDMI(3), RS-232C(1), USB(1), RF in(1), audio out(1), External speaker(1), RJ45In/Out, Crestron Certi. Compatibility, DPM (Digital Power management), Time scheduler , RTC (Real Time Clock) , NTP sync timer, SuperSign SW Compatibility-Control / Control Plus, Hospitality feature(welcom video, welcome screen-splash image, insert image), USB Auto playback, moving picture playback, setting option auto off/sleeptime, energy saving mode, motion eye care.

Commercial - TV

Model	Description
43UR640S9UD	43 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 120Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT Compliant, IPS Panel
50UR640S9UD	50 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 120Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT Compliant
55UR640S9UD	55 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 120Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT Compliant, IPS Panel
65UR640S9UD	65 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 120Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT Compliant, IPS Panel

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
75UR640S9UD	75 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 120Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT Compliant, IPS Panel
86UR640S9UD	86 UHD, 3HDMI, 1 RS232, 1 USB, Speaker, Stand, Viewing angle 178/178 NTSC, TM240Hz, Full IP Control thru network (including WOL*), DPM(Display Power Management) ,Crestron Connected , EPEAT compliant, IPS Panel

Commercial - LED SIGNAGE

Model	Description
32SM5J-B	32 FHD, IPS panel tech, 400 nit, HDMI(3), RS232C IN/OUT, RJ45(LAN) IN, IR IN, USB(1), Audio out, WebOS 6.0, 50,000 hrs of life time, 24/7 operation hours, portrait/landscape, internal memory 8.0GB, Wi-fi, temperature sensor, auto brightness sensor, local key operation, Embedded CMS,USB Plug & Play,Fail over,Background Image,Sync Mode,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Crestron Inside,Smart Energy Saving,PM mode,Wake on LAN,Network Ready,Beacon,HDMI-CEC ,
43UL3J-E	43 UHD, 3840x2160 (UHD),330nit (Typ.),Life time 30,000Hrs (Min),Operation Hours (Hours/Day)16/7,Portrait / Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Wi-Fi,Local Key Operation,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Booting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control
43UH5F-H	43UH5F -Screen Size (diagonal): 43" -28% Haze - HDMI (3) - USB 2.0 (2) - Builtin Speaker, 24/7, (50,00 hrs) -Landscape and Portraitit, Viewing Angle (178 x 178) -Auto Brightness Sensor
49UH7F-H	49UH7F -Screen Size (diagonal): 49" -Resolution: 3840 x 2160 (UHD, RGB) -Brightness: 700 nits -Warranty: 3 Year Limited Warranty -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1100:1 -Response Time (G to G): 8 ms -Input Connections: HDMI (3), DP, DVI-D, Audio, USB 2.0
50UL3J-E	50 UHD, 3840x2160 (UHD),330nit (Typ.),Life time 30,000Hrs (Min),Operation Hours (Hours/Day)16/7,Portrait / Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Wi-Fi,Local Key Operation,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Booting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control
55UL3J-E	55 UHD, 3840x2160 (UHD),330nit (Typ.),Life time 30,000Hrs (Min),Operation Hours (Hours/Day)16/7,Portrait / Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Wi-Fi,Local Key Operation,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Booting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control
55UH5F-H	55" UHD, 28% Haze, HDMI (3), DP, DVI-D, Audio, USB 2.0 (1)DP, Audio (Off/Fixed/Variable), Builtin Speaker, 24/7, (50,00 hrs), Landscape and Portraitit, Viewing Angle (178 x 178), Internal Memory 8GB (System 4GB + Available 3.6GB), Built-in Wi-Fi, Temperature Sensor, Auto Brightness Sensor, Current Sensor,Embedded CMS (USB Auto Playback, Local Contents Scheduling, Group Manager), Image Customization, Failover, Content Sync (RS232C, Local Network), Screen Share, Play via URL, OSD Rotation, Content

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Model	Description
55UH7F-H	55 UHD, Web OS 4.1, HDMI(3), DP, DVI-D, USB2.0 Type A(1), Display Port, Audio IN/OUT,RS232C IN, RJ45(LAN) IN, IR IN, Portrait / Landscape, built in WIFI, 50,000Hrs life time & 24/7 operation, 28% Haze, Internal Memory 8GB, Temperature Sensor,Auto Brightness sensor,Acceleration(Gyro) Sensor,Local Key Operation, Multi-screen PIP/PBP(4), Screen Share, Video Tag(4), Play via URL, Screen Rotation, External Input Rotation,Crestron Inside, PM mode, Wake on LAN, Beacon, HDMI-CEC ,SI Server Setting, webR
65UL3J-E	65 UHD, 3840x2160 (UHD),330nit (Typ.),Life time 30,000Hrs (Min),Operation Hours (Hours/Day)16/7,Portrait / Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Wi-Fi,Local Key Operation,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Bootting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control
65UH5F-H	65" UHD, 28% Haze, HDMI (3), DP, DVI-D, Audio, USB 2.0 (1)DP, Audio (Off/Fixed/Variable), Built-in Speaker, 24/7, (50,00 hrs), Landscape and Portrait, Viewing Angle (178 x 178), Internal Memory 8GB (System 4GB + Available 3.6GB), Built-in Wi-Fi, Temperature Sensor, Auto Brightness Sensor, Current Sensor,Embedded CMS (USB Auto Playback, Local Contents Scheduling, Group Manager), Image Customization, Failover, Content Sync (RS232C, Local Network), Screen Share, Play via URL, OSD Rotation, Content
65UH7F-H	65" UHD, 700nit, HDMI(3),DP, DVI-D, Audio In, RS232C In/Out, RJ34 In/Out, IR In, USB(1), Wi-Fi, WebOS 4.1,Life time50,000Hrs (Min.),Operation Hours (Hours/Day)24/7,Portrait / Landscape,Bezel Color:Black,Internal Memory8GB,Temperature Sensor,Auto Brightness sensor,Acceleration(Gyro) Sensor,Local Key Operation,Embedded CMS,USB Plug & Play,Fail over,Background Image,RS-232C Sync,Local Network Sync,Multi-screen: PIP/PBP,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapl
75UL3J-E	75 UHD, 3840x2160 (UHD),330nit (Typ.),Life time 30,000Hrs (Min),Operation Hours (Hours/Day)16/7,Portrait / Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Wi-Fi,Local Key Operation,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Bootting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control
75UH5F-H	75UH5F -Screen Size (diagonal): 75" -28% Haze - HDMI (3) - USB 2.0 (2) - Built-in Speaker, 24/7, (50,00 hrs) -Landscape and Portrait, Viewing Angle (178 x 178) -Auto Brightness Sensor
86UL3J-B	86 UHD, 3840x2160 (UHD),330nit (Typ.),Life time30,000Hrs (Min),Operation Hours (Hours/Day)16/7, Landscape,HDMI(3),RS232C IN,RJ45(LAN),USB2.0 Type A(2),Audio Out,RS232C OUT,Bezel Color Ashed Blue,Wi-Fi,Temperature Sensor,Auto Brightness sensor,webOS6.0,Local Contents Scheduling,Group Manager,USB Plug & Play,Fail over,Bootting Logo Image,RS-232C Sync,Local Network Sync,Screen Share,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,A
86UH5F-H	86UH5F -Screen Size (diagonal): 86" -28% Haze - HDMI (3) - USB 2.0 (2) - Built-in Speaker, 24/7, (50,00 hrs) -Landscape and Portrait, Viewing Angle (178 x 178) -Auto Brightness Sensor
98UM3E-B	Web OS, HDMI, Display Port, DVI-D, RGB
98UM5J-B	98" UHD, 500nit, HDMI(3), RJ45(LAN),USB(2), Audio Out,Back Light Type: D-LED,Life time 30,000Hrs (Typ.),Operation Hours (Hours/Day)16/7,Portrait & Landscape,Bezel Color: Black,Handle,Internal Memory1.5+16G,Wi-Fi / Bluetooth Built-in,Power Indicator,OS: Android 9.0,USB F/W update,Operation Temperature 0 C to 40 C,Operation Humidity 25%93%,Built-In Power

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Model	Description
98UH5F-H	98UH5F -Screen Size (diagonal): 98" -Resolution: 3840 x 2160 -Brightness: 500 nits -Warranty: 3 Year Limited Warranty -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1300:1 -Response Time (G to G): 8 ms -Input Connections: HDMI (3), DP, DVI-D, Audio, USB 2.0 (2)
110UM5J-B	110" UHD, 500nit, HDMI(3),RJ45(LAN),USB(2),Audio Out,Back Light Type: D-LED,Life time50,000Hrs (Typ.),Operation Hours (Hours/Day)16/7,Portrait & Landscape,Bezel Color:Black,Bezel Width: 17mm,Wi-Fi / BluetoothBuilt-in,Internal Memory: 1.5+16G,Power Indicator,Local Key Operation,OS: Android 9.0,USB F/W update,Operation Temperature 0 C to 40 C,Operation Humidity 25%93%,Built-In Power

Commercial - OLED

Model	Description
55EF5G-P	HDMI, DP, USB 2.0 (2), RS232C In/out, RJ45 In/out, IR In
55EF5G-L	HDMI, DP, USB 2.0 (2), RS232C In/out, RJ45 In/out, IR In
55EW5G-V	55" Transparent FHD OLED, HDMI(2),DP,RS232C IN/Out,RJ45 In/Out, IR In, USB(2), DP, Audio Out, Protection Glass Depth 3.0mm, Chemical strengthening, Ani-reflective(film), Shatter Proof, Internal Memory 16 GB, Temperature Sensor, Web OS4.0, Embedded CMS,USB Plug & Play,Fail over,RS-232C Sync,Local Network Sync,Video Tag,Screen Rotation,External Input Rotation,Gapless Playback,Tile Mode Setting,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control Manager,Crestron Inside,PM mode,W
55EW5PG-S	55 Transparent OLED,1920x1080 (FHD),Life time30,000 Hrs (Typ.),Operation Hours (Hours/Day)18/7 (Moving Content Only),Portrait / LandscapeO,HDMI,DP,RS232C IN,RS232C OUT,RJ45(LAN),USB,DP Out,Audio Out,Bezel ColorTransparent,Internal Memory16GB,Wi-Fi,Temperature Sensor,Embedded CMS,USB Plug & Play,Fail over,Video Tag,Gapless Playback,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Status Mailing,Control Manager,Crestron Inside,Wake on LAN,PM mode,HDMI-CEC ,SI Server Setting,Pro:Idiom,Operation Tem
55EJ5G-B	55EJ5G -Brightness(Typ.): 400 cd/m ² (APL 25%) -Bezel: 0.9 mm (Even, Off bezel) -Depth: 4.9mm (Head) -Interface: HDMI/ USB 2.0(2)/ DP/ Audio Out/ RS232C/ RJ45/ IR
65EP5G-B	65 OLED Pro Picture -Adjust(OLED Light Brightness Contrast Chroma Sharpness Tint) Color Temp(VAR Temp./9300K/6500K/5400K/3200K/D65(6504K)/C(6774K)/D-Cinema(6302K)) R/G/B Gain(-100 ~ 100) Transfer Matrix(Auto / BT.709 / BT.601 / BT.2020) Mastering Peak(Auto / 0 / 400 / 540 / 700 / 1000 / 2000 / 3000 / 4000 / 10000) SDI Color Format(Auto / RGB444 / YCbCr444 / YCbCr422) SCAN(Zero Scan /Over Scan / Under Scan / Pixel to Pixel) AFD (Active Format Description) Aspect Ratio(Full/16:9/4:3/14:9/13:9/1.8

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Commercial - Out Door / Semi-Out Door

Model	Description
22SM3G-B	<p>22SM3G-B</p> <ul style="list-style-type: none"> -Screen Size (diagonal): 21.5" -Resolution: 1920 x 1080 -Brightness: 250 nits -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1000:1 -Response Time (G to G): 14 ms -Input Connections: HDMI (2), USB 2.0 Type A, Audio In -Daily Operation: 16 / 7 -Lifetime: 30,000 hours
22XE1J-B	<p>Screen Size 21.5", Native Resolution 1920x1080(FHD), 1500nit (Typ, w/ Glass), Life time 70,000 Hrs (Typ), Operation Hours (Hours/Day) 24/7, Portrait / Landscape, HDMI, RS232C IN, RJ45(LAN), USB 2.0 Type A (1), External Speaker Out, Internal Memory 16GB, Wi-Fi, Temperature Sensor, Auto Brightness sensor, Humidity Sensor, Acceleration(Gyro) Sensor, Power Indicator, FAN, webOS 4.1, Embedded CMS, USB Plug & Play, Fail over, Background Image, Video Tag, Play via URL, Screen Rotation, External Input Rotation, Smart Energy Saving, PM m</p>
49XE4F-M	<p>49XE4F</p> <ul style="list-style-type: none"> -Screen Size (diagonal): 49" -Resolution: 1920 x 1080 -Brightness: 3200 nits -Warranty: 3 Year Limited -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1300:1 -Response Time (G to G): 8 ms -Input Connections: HDMI, DP, RGB, USB
49XS4J-B	<p>49" FHD, HDMI(2), DP, RS232C In/Out, RJ45 In, IR In, USB(1), External Speaker out, 1920x1080 (FHD), Operation Hours (Hours/Day) 24/7, Life time 50,000 Hrs (Typ), Portrait / Landscape, Internal Memory 16GB, Built-in Wi-Fi, Temperature Sensor, Auto Brightness sensor, Acceleration(Gyro) Sensor, Local Key Operation, FAN, webOS 4.1, Embedded CMS, USB Plug & Play, Fail over, Background Image, Sync Mode, Multi-screen PIP/PBP, Screen Share, Video Tag, Play via URL, Screen Rotation - External Input Rotation, Gapless Playback, Tile</p>
55XE4F-M	<p>55XE4F</p> <ul style="list-style-type: none"> -Screen Size (diagonal): 55" -Resolution: 1920 x 1080 -Brightness: 3200 nits -Warranty: 3 Year Limited -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1200:1 -Response Time (G to G): 8 ms -Input Connections: HDMI, DP, RGB, USB
55XS4J-B	<p>55" FHD, HDMI(2), DP, RS232C In/Out, RJ45 In, IR In, USB(1), External Speaker out, 1920x1080 (FHD), Life time 50,000 Hrs (Typ), Operation Hours (Hours/Day) 24/7, Rotation Portrait / Landscape, lay, Fail over, Background Image, Sync Mode, Multi-screen PIP/PBP, Screen Share, Video Tag, Play via URL, Screen Rotation, External Input Rotation, Gapless Playback, Tile Mode Setting, Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, Smart Energy Saving, PM mode, Wake on LAN, Network Ready, Beaco</p>
75XE3C-B	<p>75XE3C</p> <ul style="list-style-type: none"> -Screen Size (diagonal): 75" -Resolution: 3840 x 2160 (UHD) M+ (WRGB) -Brightness: 3000 nits -Panel Type: IPS -Aspect Ratio: 16:9 -Response Time (G to G): 8 ms -Input Connections: HDMI, DP, DVI-D, Audio In, USB 3.0, SD Card

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Model	Description
75XS4G-B	HDMI(2), DP, USB2.0 Type A (1), RS232C IN/out, RJ45(LAN)In/Out, IR IN, External Speaker Out L/R, Bezel Width -Even bezel : 13.8mm, Internal Memory 16GB, Built in Wi-Fi, Temperature Sensor, Auto Brightness sensor, Acceleration(Gyro) Sensor, webOS4.1, Multi-screen PIP/PBP(2), Screen Share, Video Tag(4), Play via URL, Screen Rotation, External Input Rotation, 24/7/50,000 Hrs life time, Operation Temperature - 0 C to 40C , Operation Humidity -10 % to 80 %, Power Supply AC 100-240V~, 50/60Hz,

Commercial - TOUCH

Model	Description
55TC3CG-H	55TC3CG -Screen Size (diagonal): 55" -Resolution: 3840 x 2160 (UHD) -Brightness: 350 nits -Warranty: 3 Year Limited -Panel Type: IPS Capacitive Touch -Aspect Ratio: 16x9 -Contrast Ratio: 1100:1 -Input Connections: HDMI (x2), DP, RS-232, RJ45, IR-In, USB 2.0
65TR3DJ-B	65" UHD, IPS Panel, Anti Glare, 7H(Mohs) surface treatment(Haze), 8ms (G to G) response time, 30,000 Hrs of life time, 16/7(hours/day) operation hours, Landscape, HDMI(3), USB- USB3.0 Type A(3) & USB2.0 Type A(3) , RGB, Android 8.0, Audio In/out, RS232C IN, RJ45(LAN) IN, Touch USB(2), Handle, VESATM Standard Mount Interface, Internal Memory 16(GB), Built in WIFI, Power indicator, Local Key operation, Android 8.0, Screen Share, Operation temp 0 C to 40 C, Operation Humidity 10% to 80%, OPS typ
65TR3DJ-WM	Bundle - 1 unit of 65TR3DJ-B Display with stand accessory WM-L000S.
65TR3DJ-ST	Bundle - 1 unit of 65TR3DJ-B Display with stand accessory ST-000F.

Display - Outdoor

Model	Description
65EP5G-ACS.EUS	65EP5G bundle with stand(1 display 65EP5G-B + 1 stand ACC-S-EP5G)

Commercial - TOUCH

Model	Description
75TR3DJ-B	75" UHD, IPS Panel, Anti Glare, 7H(Mohs) surface treatment(Haze), 8ms (G to G) response time, 30,000 Hrs of life time, 16/7(hours/day) operation hours, Landscape, HDMI(3), USB- USB3.0 Type A(3) & USB2.0 Type A(3) , RGB, Android 8.0, Audio In/out, RS232C IN, RJ45(LAN) IN, Touch USB(2), Handle, VESATM Standard Mount Interface, Internal Memory 16(GB), Built in WIFI, Power indicator, Local Key operation, Android 8.0, Screen Share, Operation temp 0 C to 40 C, Operation Humidity 10% to 80%, OPS typ
75TR3DJ-WM	Bundle - 1 unit of 75TR3DJ-B Display with stand accessory WM-L000S.

Display - Transparent

Model	Description
WM-B640S	Dedicated bracket for double-sided installation for 75XS4G and LG 65/55/49 inches UH7 Series, 65/55/49 inches UH5/UM3 Series

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Commercial - TOUCH

Model	Description
75TR3DJ-ST	Bundle - 1 unit of 75TR3DJ-B Display with stand accessory ST-000F.
86TR3DJ-B	65" UHD, IPS Panel, Anti Glare, 7H(Mohs) surface treatment(Haze), 8ms (G to G) response time, 30,000 Hrs of life time, 16/7(hours/day) operation hours, Landscape, HDMI(3), USB- USB3.0 Type A(3) & USB2.0 Type A(3) , RGB, Android 8.0, Audio In/out,RS232C IN, RJ45(LAN) IN, Touch USB(2), Handle, VESATM Standard Mount Interface, Internal Memory 16(GB), Built in WIFI, Power indicator, Local Key operation, Android 8.0, Screen Share, Operation temp 0 C to 40 C, Operation Humidity 10% to 80%, OPS typ
86TR3DJ-WM	Bundle - 1 unit of 86TR3DJ-B Display with stand accessory WM-L000S.
86TR3DJ-ST	Bundle - 1 unit of 86TR3DJ-B Display with stand accessory ST-000F.

One Quick Series - Quick Works

Model	Description
55CT5WJ-B	Landscape onlyKey Feature(Windows)-Internal Memory8GB3840x2160 (UHD)U-IPSLife time50000HrsOperation Hours (Hours/Day)24/7Connectivity(webOS): HDMI(2)DPUSB-Type CRS232C INRJ45(LAN)IR INUSB2.0 Type A(1)RS232C OutRJ45(LAN) Connectivity(Windows): RJ45(LAN)USB3.1 Type A(2) USB Type C(1)Temperature SensorAuto Brightness sensorLocal Key OperationwebOS4.1Background Image-Booting Logo ImageNo Signal ImageScreen RotationExternal Input RotationCrestron InsideSmart Energy SavingPM modeWake on LANHDMI-CEC B

Commercial - STRETCH

Model	Description
86BH5F-B	86" UHD Ultra stretch, 500 nit, HDMI(3), DP, DVI-D, USB2.0(2), Audio In,RS232C IN,RJ45(LAN),IR IN,DP Out,Audio Out,RS232C OUT,RJ45(LAN),Wi-Fi,webOS 4.0 (SCAP : not support),Embedded CMS,USB Plug & Play,Background Image,PBP,Screen Rotation,External Input Rotation,Beacon,HDMI-CEC ,SuperSign Control / Control+,SuperSign WB,SuperSign Media Editor,Signage 365 Care,50,000Hrs (Typ.),24/7
86BH5F-M	86" UHD Ultra stretch, 500 nit, HDMI(3), DP, DVI-D, USB2.0(2), Audio In,RS232C IN,RJ45(LAN),IR IN,DP Out,Audio Out,RS232C OUT,RJ45(LAN),Wi-Fi,webOS 4.0 (SCAP : not support),Embedded CMS,USB Plug & Play,Background Image,PBP,Screen Rotation,External Input Rotation,Beacon,HDMI-CEC ,SuperSign Control / Control+,SuperSign WB,SuperSign Media Editor,Signage 365 Care,50,000Hrs (Typ.),24/7
88BH7G-B	88" UHD Ultra stretch, 700nit, Web OS, HDMI (3), USB(2), Display Port(1), DVI-D(1), Audio In(1), RS232C IN,RJ45(LAN),IR IN,DP Out,Audio Out,RS232C OUT,RJ45(LAN), Built in WIFI, Web OS 4.0,Embedded CMS, USB Plug & Play,Background Image,RS-232C Sync,Local Network Sync,PBP(4),Video Tag(4),Screen Rotation,External Input Rotation,Gapless Playback,Beacon,HDMI-CEC ,SI Server Setting,webRTC,Pro:Idiom,Operation Hours (Hours/Day) 24/7

Commercial - Video Walls

Model	Description
55SVH7PF-H	HDMI (2), DP, DVI-D, RGB, Audio, USB 2.0, RS232C In/out, RJ45 In/out, IR In, 24 Hrs, Bezel to Bezel .88mm, Internal Memory 8GB (System 4GB, Available 4GB), Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode @ Tile Mode, ISM Method, DPM Select, Smart Energy Saving, Contents Scheduling(USB, Inte
49VL5G-M	HDMI,DP,DVI-D,Audio In,RS232C IN,RJ45(LAN),IR IN,USB,DP Out,Audio Out,RS232C OUT,Temperature Sensor,Local Contents Scheduling,USB Plug & Play,Fail over,Booting Logo Image,No Signal Image,RS-232C Sync,Screen Rotation,Tile Mode Setting,Setting Data Cloning,SNMP,ISM Method,Auto Set ID,Crestron Inside,Smart Energy Saving,PM mode,Wake on LAN,HDMI-CEC ,SI Server Setting,SuperSign CMS,SuperSign Control / Control+,SuperSign WB,SuperSign Media Editor,Signage 365 Care, Portrait / Landscape, Operation Hour

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
55VL5F-A	55VL5F -Screen Size (diagonal): 55" -Resolution: 1920 x 1080 -Brightness: 500 nits -Warranty: 3 Year Limited Warranty -Panel Type: IPS -Aspect Ratio: 16:9 -Contrast Ratio: 1200:1 -Response Time (G to G): 8 ms -Input Connections: HDMI(x2), DP, DVI-D, Audio, USB 2.0
55VSM5J-H	55"FHD Video-Wall,Even bezel : 0.44mm, HDMI(2), DP(1), DVI-D(1), Audio In, RS232C IN/Out, RJ45(LAN), IR IN, USB(1), WebOS 4.1, Operation Hours (Hours/Day)24/7,Portrait / Landscape,Bezel Color: Black,Handle,Internal Memory8GB,Temperature Sensor,BLU Sensor,Acceleration(Gyro) Sensor,Local Key Operation,Embedded CMS,USB Plug & Play,Fail over,RS-232C Sync,Local Network Sync,Video Tag,Play via URL,Screen Rotation,External Input Rotation,Gapless Playback,Tile Mode Setting,Setting Data Cloning,SNMP,ISM

Commercial - Video Wall Bundle

Model	Description
49VL5GMW-4P	2x2 49VL5G-M w/Peerless mount
49VL5GMW-9P	3x3 49VL5G-M w/Peerless mount
49VL5GMW-4C	2x2 49VL5G-M bundle with Crimson mount
49VL5GMW-9C	3x3 49VL5G-M bundle with Crimson mount
55VL5FAW-4C	2x2 55VL5F-A bundle with Crimson mount
55VL5FAW-4P	Peerless Mount SKU : DS-VW775
55VL5FAW-9C	3x3 55VL5F-A bundle with Crimson mount
55VL5FAW-9P	Peerless Mount SKU : DS-VW775
55VM5EW-4P	Peerless Mount SKU : DS-VW775
55VM5EW-9P	Peerless Mount SKU : DS-VW775
55VM5J-H	55 FHD Video Wall, 1,920 X 1,080 (FHD), 500nit (Typ.), IPS Panel Technology, Life time 60,000Hrs (Typ.) / 50,000Hrs (Min.), Operation Hours (Hours/Day) 24/7, Portrait / Landscape, HDMI(2), HDCP2.2, DP, DVI-D, Audio In, Audio Out, RS232C IN, RS232C OUT, RJ45(LAN), IR IN, USB2.0 Type A(1), Bezel Color Black, Bezel Width B2B : 1.74mm (Panel Bezel to Panel Bezel), 1.3mm(T/L), 0.44mm(B/R), A2A : 2.49mm (Active area to Active area), 1.75mm(T/L), 0.74mm(B/R), Handle, Internal Memory 8GB, Temperature Se
55VSM5JW-4P	2x2 55VSM5J-H w/Peerless mount
55VSM5JW-9P	3x3 55VSM5J-H w/Peerless mount
55VSM5JW-4C	2x2 55VSM5J-H bundle with Crimson mount
55VSM5JW-9C	3x3 55VSM5J-H bundle with Crimson mount

Commercial - Accessories

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Model	Description
WM-L000S	Accessory - Wall mount for TR3DJ models, max loading 350
OPJSJ-5LDJA	OPS Media Player for TR3DJ models, i5 Windows 10 OPS slot-in PC for CreateBoard TR series
WP402-B	Commercial Signage Media Player_Sigage webOS box (4.0) (UHD OUTPUT)
BP350.EUSALLF? Order SKU #BP350.EUSALLF	BP350 -BLU-RAY/DVD/CD Playback -Premium Content Providers -Built-in WiFi

Commercial - Accessory - OLED Accessory

Model	Description
ACC-CC-EF5E	ACC-CC-EF5E -Curvature Calibrator -Optional Accessory for 55EF5E/ 55EF5F/ 55EF5G OLED Signage -Supported Curvature: Up to 1,000R(Concave/Convex) -On-site Customization

Commercial - Accessory - Speakers

Model	Description
SP-5000	Optional Speakers for SE3B-B/SM5B-B
SP-5200	Optional Speakers for UH5B
ST-000F	Accessory - Mobile trolley cart for TR3DJ models, max loading 260
ST-1300F	Floor Stand
ST-1361FH	Motorized Stand (old model ST-1360F)
ST-1362FH	Motorized Stand - for 136" LAEC015

Commercial - Accessory - Stands

Model	Description
ACC-S-EW5F	Stand for OLED display, 2pc stand set for OLED Monitor
ST-201T	Stand for 55/49UH5
ST-322T	Stand for 32SE/SM
ST-432T	Stand for 43SE/SM
ST-43HT	1 Pole Desktop Stand for One:Quick Flex (43HT3WJ-B)
ST-43HF	Movable floor stand for One:Quick Flex (43HT3WJ-B)
ST-492T	Stand for 49SE/SM

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
ST-651T	Stand for 65LS33A/65UH5
ST-652T	Stand for 55&65SE/SM
ST-653T	Stand for 43",49", 55", 65" UH5F-H
ST-653TW	Stand for 43",49", 55", 65" UH5F-H

Commercial - Accessory - Video Walls

Model	Description
LPLG001-FV	External Power box for 55SVH7PF

IT Products - PC Monitors

Model	Description
24CN650N-6A	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
24CN650N-6N	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
24CN650W-AP **NEW**	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 8GB DDR4, 128GB eMMC, IPS
24CN670IK6N **NEW**	24" LG Thin CLIENT IGEL PRE-INSTALLED AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
43BN70U-B	43" LG MONITOR, 3840X2160, 16:9 IPS, HDR10, USB-C, TAA
43HT3WJ-B	Portrait / LandscapeKey Feature(Windows)-Internal Memory4GB3840x2160 (UHD)U-IPSLife time50000HrsOperation Hours (Hours/Day)24/7Connectivity(webOS): HDMI(2)DPUSB-Type CRS232C INRJ45(LAN)IR INUSB2.0 Type A(1)RS232C OutRJ45(LAN) Connectivity(Windows): RJ45(LAN)USB3.1 Type A(2) USB Type C(1)Temperature SensorAuto Brightness sensorLocal Key OperationwebOS4.1Background Image-Booting Logo ImageNo Signal ImageScreen RotationExternal Input RotationCrestron InsideSmart Energy SavingPM modeWake on LANHDMI
22BK430H-B	21.5IN LED LCD 1920X1080 16:9 IPS
22BL450Y-B	22" LG MONITOR, 1920X1080, 16:9 IPS, DISPLAY PORT
22BL450Y-W	22" LG MONITOR, 1920X1080, 16:9 IPS, DP
24BK430H-B	23.8IN LED LCD 1920X1080 16:9 IPS
24BK550Y-I	24IN 1920X1080 16:9 IPS DP
24BK750Y-B	23.8IN LED LCD 1920X1080 16:9 IPS
24BL450Y-B	24" LG MONITOR, 1920X1080, 16:9 IPS, DISPLAY PORT
24BL650C-B	24" LG MONITOR, 1920X1080, 16:9 IPS, USB-C
24BP750C-B	24" LG MONITOR, 1920 x 1080, 16:9 IPS, USB-C, HDMI, DP
24BP75Q-B	24" LG MONITOR, 2560 x 1440, 16:9 IPS, USB-C, HDMI, DP

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
27BK400H-B	27IN LED LCD 1920 X 1080 16:9 IPS
27BK430H-B	27IN LED LCD 1920X1080 16:9 IPS
27BK550Y-I	27IN 1920X1080 16:9 IPS DP
27BK750Y-B	27IN LED LCD 1920X1080 16:9 IPS

Desktop Monitor - LED/LCD

Model	Description
34CN650I-6N **NEW**	34" LG THIN CLIENT IGEL PRE-INSTALLED AIO MONITOR, 2560X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB eMMC, IPS, TAA, HW TPM

IT Products - PC Monitors

Model	Description
27BL85U-W	27" LG MONITOR, 3840X2160, 16:9 IPS, FREESYNC, USB-C
27BL450Y-B	27" LG MONITOR, 1920X1080, 16:9 IPS, DP
27BL650C-B	27" LG MONITOR, 1920X1080, 16:9 IPS, USB-C
27BL55U-B	27" LG MONITOR, 3840X2160, 16:9 IPS, FREESYNC, DP, TAA
27BN88Q-B	27" LG MONITOR, 2560x1440, 16:9 IPS, USB-C, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (2 DOWN) ERGO STAND
32BL75U-W	32" LG MONITOR, 3840X2160, 16:9 VA, FREESYNC, USB-C
32EP950-B	32" LG OLED MONITOR, 3840 X 2160, 16:9 OLED, HDMI, DISPLAY PORT 1.4 (2), USB 3.0 (1 UP, 3 DOWN), USB Type-C
BF50NST	4K WUXGA, 5000 Ansi, Smart Laser projector, WebOS & Magic remote, HDR10, TruMotion, IP control, DICOM, HDBaseT
BF60PST	ProBeam BF60PST 6000 lumens WUXGA laser projector, 20000 hrs, IP control, DICOM, HDBaseT, TAA Compliant
BU50NST	4K UHD, 5000 Ansi, Smart Laser projector, WebOS & Magic remote, HDR10, TruMotion, IP control, DICOM, HDBaseT
BU53PST	ProBeam BU53PST 5000 lumens 4K UHD short throw laser projector, 20000 hrs, TruMotion, IP control, HDBaseT, TAA Compliant, 4K UHD (3840x2160) , WiFi & Bluetooth included. No wireless by special order request.
BU60PST	ProBeam BU60PST 6000 lumens 4K UHD laser projector, 20000 hrs, TruMotion, IP control, DICOM, HDBaseT, TAA Compliant
HU85LS	4K UHD UST, 2700 Ansi, Smart Laser home cinema projector, WebOS & Magic remote, HDR10, TruMotion, IP control
24CK550W-3A	23.8 IN LED CLOUD THIN CLIENT 1920X1080 IPS
24CK550N-3A	24IN CLOUD THIN CLIENT 1920X1080 IPS
24CK550Z-BP	24" LG ZERO CLIENT AIO MONITOR, TERA 2321 PCOIP, 1920 X1080, DISPLAY PORT USB, IPS, TAA
24CK560N-3A	24" LG THIN CLIENT AIO MONITOR, 1920X1080, AMD PRARIE FALCON GX 212JJ, 4GB DDR, 32GB SSD, IPS, TAA, IEC60601 Medical Certification

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
24CN650I-6N	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
24CN670NK6A	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
24CN670NK6N	24" LG Thin CLIENT AIO MONITOR 1920X1080, Intel(R) Celeron J4105, 4GB DDR4, 16GB eMMC, IPS
27CN650N-6A	27" LG THIN CLIENT AIO MONITOR, 1920X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB SSD, IPS, TAA, HW TPM
27CN650N-6N	27" LG THIN CLIENT AIO MONITOR, 1920X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB eMMC, IPS, TAA, HW TPM
27EP950-B	27" LG OLED MONITOR, 3840 X 2160, 16:9 OLED, HDMI, DISPLAY PORT 1.4 (2), USB 3.0 (1 UP, 3 DOWN), USB Type-C
27BK67U-B	27IN 3840x2160 16:9 IPS USB-C
27BN85UN-B	27" LG MONITOR, 3840X2160, 16:9 IPS, HDMI 2.0 (2) USB-C
27BN88U-B	27" LG MONITOR, 3840x2160, 16:9 IPS, USB-C, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (2 DOWN) ERGO STAND

Accessory - General

Model	Description
CL600I-6N	LG THIN CLIENT BOX, INTEL CELERON QUAD CORE, 4GB DDR4, 16GB eMMC, TAA

IT Products - PC Monitors

Model	Description
32BL95U-W	32IN 3840 X 2160 16:9 NANO IPS FREESYNC HDR10 THUNDERBOLT
32BN50U-B	32" LG MONITOR, 3840X2160, 16:9 , VA, HDMI 2.0 (2) HDR10
32BN67U-B	32" LG MONITOR, TRUE 4K 3840X2160, 16:9 IPS, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (1UP/2 DOWN)
32BN88U-B	32" LG MONITOR, TRUE 4K 3840X2160, 16:9 IPS, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (2 DOWN), USB Type-C ERGO STAND
32BP88Q-B **NEW**	32" LG QHD MONITOR, 2560 x 1440, 16:9 IPS, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (2 DOWN), USB Type-C ERGO STAND
24GL65B-B	24" LG GAMING MONITOR, 1920 X 1080, 16:9 TN, FREESYNC, DISPLAY PORT
27GN75B-B	27" LG GAMING MONITOR, 1920 x 1080, 16:9 IPS, FREESYNC, DP
27GN95B-B	27" LG GAMING MONITOR, 3840 x2160, 16:9 NANO IPS, FREESYNC,HDMI, DP
32GK65B-B	32" LG GAMING MONITOR, 2560 X 1440, 16:9 VA, G-SYNC, DISPLAY PORT
38GN95B-B	38" LG CURVED GAMING MONITOR, 3840 X 1600, 21:9 NANO IPS, G-SYNC, DP
40BP95C-W **NEW**	40" LG MONITOR, 5120 x 1440, 21:9 IPS, HDR10, USB-C

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
49BL95C-WY	49" LG MONITOR, 5120 x 1440, 32:9 IPS, USB-C
29BN650-B	29" LG MONITOR, 2560X1080, 21:9 IPS, HDMI, DP
34BK95U-W	34IN 5120X2160 21:9 NANO IPS HDR10 THUNDERBOLT
34BL650-B	34" LG MONITOR, 2560 x 1080, 21:9 IPS, FREESYNC, DISPLAY PORT
34BL85C-B	34" LG MONITOR, 3440X1440, 16:9 IPS, HDR10, DISPLAY PORT
34BN670-B	34" LG MONITOR, 2560X1080, 21:9 IPS, DP, HDMI
34BN770-B	34" LG MONITOR, 3440X1440, 21:9 IPS, HDMI, DP
34BN77C-B	34" LG MONITOR, CURVED 3440X1440, 21:9 IPS, HDMI, DP
34BN780-B	34" LG MONITOR, 3440X1440, 21:9 IPS, HDMI 2.0 (2), DP, USB 3.0 (1UP, 2DOWN) ERGO STAND
34BP65C-B	34" LG MONITOR, Curved, 3440X1440, 21:9 VA, HDMI 2.0 (2), DP
34BP85C-B	34" LG MONITOR, Curved, 3440X1440, 21:9 IPS, HDMI 2.0 (2), DP, USB Type-C, USB 3.0
34BP85CN-B	34" LG MONITOR, Curved, 3440X1440, 21:9 IPS, HDMI 2.0 (2), DP, USB Type-C, USB 3.0
34BP88CN-B	34" LG MONITOR, Curved, 3440X1440, 21:9 IPS, HDMI 2.0 (2), DP, USB Type-C, USB 3.0, ERGO STAND
34CN650N-6A	34" LG THIN CLIENT AIO MONITOR, 2560X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB SSD, IPS, TAA, HW TPM
34CN650N-6N	34" LG THIN CLIENT AIO MONITOR, 2560X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB eMMC, IPS, TAA, HW TPM
35BN75CN-B	35" LG MONITOR, 3440X1440, 21:9 VA, USB-C, DP, HDMI
38BN95C-W	38" LG MONITOR, 3840X1600, 21:9 NANO IPS, HDMI, DP THUNDERBOLT
38BP85C-W	38" LG MONITOR, Curved, 3840X1600, 21:9, IPS, USB Type-C, HDMI, DP, USB

IT Products - Laptops

Model	Description
14ZT90P-G.AX33U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
14ZT90P-G.AM33U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
14ZT90P-G.AM13U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
14ZT90P-G.AX13U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G

Starin is your Supply Partner. To place your order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
14ZT90P-G.AM12U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
17ZT90P-G.AX33U1	17" LG GRAM LIGHTWEIGHT NOTEBOOK, HDD TPM, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
17Z90P-N.APS5U1	17" LG GRAM LIGHTWEIGHT NOTEBOOK,HW TPM, WINDOWS 10PRO, CORE I7, 16GB DDR, 512GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
17Z90P-N.APB7U1	17" LG GRAM LIGHTWEIGHT NOTEBOOK,HW TPM, WINDOWS 10PRO, CORE I7, 16GB DDR, 1TB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
16Z90P-N.APS5U1	16" LG GRAM LIGHTWEIGHT NOTEBOOK, HW TPM, WINDOWS 10PRO, CORE I7, 16GB DDR, 512GB SSD, FINGERPRINT SENSOR, IPS,MIL-STD810G
16Z90P-N.APB7U1	16" LG GRAM LIGHTWEIGHT NOTEBOOK, HW TPM, WINDOWS 10PRO, CORE I7, 16GB DDR, 1TB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
15Z90P-N.APS7U1	15" LG GRAM LIGHTWEIGHT NOTEBOOK, HW TPM, WINDOWS 10PRO, CORE I7, 16GB DDR, 1TB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G
14Z90P-N.APS3U1	14" LG GRAM LIGHTWEIGHT NOTEBOOK, HW TPM, WINDOWS 10PRO, CORE I5, 8GB DDR, 256GB SSD, FINGERPRINT SENSOR, IPS, MIL-STD810G

IT Products - Medical Monitors

Model	Description
21HK512D-B	21HK512D-B -Designed Specifically for Medical Diagnostic Reading -DICOM Part 14 GSDF -Resolution 2048 x 1536 -Brightness 1000 cd/m ² (Typ) -Contrast Ratio 1400:1 -Response Time 30ms (Typ) -Tilt/Swivel/Height/Pivot Adjustable -VESA Compliant Wall Mountable -TAA Compliant -FDA 510(k) Class II (pending) -3-Year Limited Warranty (SWAP)
21HQ513D-B	21" LG MEDICAL IPS 3MP DIAGNOSTIC MONITOR 2048 X 1536 DP FDA 510K CLASS II
27HJ712C-W	27HJ712C-W -Designed Specifically for the Healthcare Professionals -UL Medical Grade Listed -DICOM part 14 -Native Display Resolution 3840 x 2160 -Contrast Ratio 1000:1 -14ms(Typ.) Response Time -Six Axis Control -Brightness Stabilization -Flicker Safe -Reader Mode -VESA™ Compliant Wall Mountable -3-Year Limited Warranty Parts/Labor/Backlight

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz

Pricing subject to change without notice.

Model	Description
27HJ713C-B	27HJ713C-B -Designed Specifically for the Healthcare Professionals -UL Medical Grade Listed -DICOM part 14 -Native Display Resolution 3840 x 2160 -Contrast Ratio 1000:1 -14ms(Typ.) Response Time -Six Axis Control -Brightness Stabilization -Flicker Safe -Reader Mode -VESA™ Compliant Wall Mountable -3-Year Limited Warranty Parts/Labor/Backlight
27HJ713S-W	27HJ713S-W -Designed Specifically for the Operating Room -UL Medical Grade Listed -DICOM part 14 -Native Display Resolution 3840 x 2160 -Contrast Ratio 1000:1 -14ms(Typ.) Response Time -Six Axis Control -Brightness Stabilization -VESA™ Compliant Wall Mountable -3-Year Limited Warranty Parts/Labor/Backlight
27HK510S-W	27HK510S-W -Designed Specifically for the Operating Room -UL Medical Grade Listed -FDA Class 2 -TAA Compliant -Native Display Resolution 1920 x 1080 -Contrast Ratio 1000:1 -14ms (Typ.) Response Time -Six Axis Control -Brightness Stabilization -VESA™ Compliant Wall Mountable -3-Year Limited Warranty Parts/Labor/Backlight
32HL512D-B	32" LG MEDICAL IPS 8MP DIAGNOSTIC MONITOR 3480X2160 DP FDA 501K (starting 2020) TAA
32HL710S-W	32" LG MEDICAL IPS 4K SURGICAL MONITOR 3480X2160 SRGB 115% DICOM14 IP35&IP32 FDA CLASS I (starting November) TAA
32LT340C9UB	32 HD, HDMI, 1 RS232, USB, Speaker, Stand, Viewing angle 178/178 NTSC, Refresh rate 60Hz, DPM(Display Power Management)
32HL714S-W	32" LG MEDICAL IPS 4K SURGICAL MONITOR 3480X2160 DP FDA CLASS I, 12G SDI
31HN713D-B	31" LG MEDICAL ANTI-GLARE, 3H DIGNOSTIC MONITOR 4200 X 2800 (3:2) CLASS II FDA 510K

Accessory - Medical Monitor Extended Service

Model	Description
MM19E10000U	19" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage
MM19E1S100U	19" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage, Quick-Swap (24 Hrs)
MM19E20000U	19" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
MM19E2S100U	19" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage, Quick-Swap (24 Hrs)
MM21E10000U	21" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage
MM21E1S100U	21" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage, Quick-Swap (24 Hrs)
MM21E20000U	21" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage
MM21E2S100U	21" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage, Quick-Swap (24 Hrs)
MM27E10000U	27" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage
MM27E1S100U	27" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage, Quick-Swap (24 Hrs)
MM27E20000U	27" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage
MM27E2S100U	27" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage, Quick-Swap (24 Hrs)
MM32E10000U	32" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage
MM32E1S100U	32" Medical Monitor, 1 Year Extended Service Term, 4 Years Total Coverage, Quick-Swap (24 Hrs)
MM32E20000U	32" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage
MM32E2S100U	32" Medical Monitor, 2 Years Extended Service Term, 5 Years Total Coverage, Quick-Swap (24 Hrs)

IT Products - Cloud Devices

Model	Description
CK500W-3A	VMWARE AMD PRARIE FALCON GX-212JJ
CK500N-3C	LG THIN CLIENT BOX, VMWARE, AMD PRARIE FALCON GX-212JJ, 4GB DDR4, 32GB SSD, TAA
CL600N-6A	LG THIN CLIENT BOX, INTEL CELERON QUAD CORE, 4GB DDR4, 16GB eMMC, TAA
CL600N-6N	LG THIN CLIENT BOX, INTEL CELERON QUAD CORE, 4GB DDR4, 16GB eMMC, TAA
CBV42-BP	LG ZERO CLIENT BOX, TERA2321 PCOIP, BRACKET, 1920 X 1200, DISPLAY PORT USB, IPS, TAA

Hospitality - TV

Model	Description
55UT340H9UA	Commercial Lite, 4K UHD, Non-Pro:idiom, Instant-on mode, One-pole Commercial stand (65" Non-swivel), 2yr w'ty +

-

Model	Description
LAT140GT82S	Film Large (655*492), 1film / box
CSAB-00914 **NEW**	4K System Controller_LSAB009

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz



Pricing subject to change without notice.

Model	Description
LSAB012-M12 **NEW**	1.25mm,Peak. 1,600nit Typ. 800nit,COB,600 x 337.5 x 44.9_Main Bottom Standard
LSAA015-UX2	Main - Signal+Power Redundancy(Top)
LSAA015-TX2	Secondary - Siganal + Power Redundancy
LSAA015-QX2	Main - Signal Redundancy(Top)
LSAA015-NX2	Main - Siganal +Power Redundancy(Bottom)

Commercial - Commercial Lite LED/LCD

Model	Description
75UR640S0UD	75 UHD 3HDMI 1 RS232 1 USB Speaker Stand Viewing angle 178/178 NTSC Refresh rate 120Hz Full IP Control thru network (including WOL*) DPM(Display Power Management) Crestron Connected EPEAT Compliant IPS Panel

Commercial - OLED

Model	Description
55EW5TK-A	55Transparent Touch OLED, 1920x1080 (FHD),Brightness 150/400nit (APL 100%/25%, Without Glass), Life time30,000 Hrs (Typ.),Operation Hours (Hours/Day)18/7 (Moving Content Only),Portrait / Landscape,HDMI,DP,RS232C IN,RS232C OUT,RJ45(LAN),IR IN,USB,Audio Out,Bezel ColorMatt Silver,Internal Memory16GB,Temperature Sensor,webOS4.0,Embedded CMS,USB Plug & Play,Video Tag,Screen Rotation,Gapless Playback,HDMI-CEC ,SI Server Setting,Pro:Idiom,Operation Temperature0 C to 40 C,Operation Humidity10 % to

IT Products - PC Monitors

Model	Description
24BP450Y-I	24" LG MONITOR, 1920X1080, 16:9 IPS, HDMI, DP

IT Products - UHD and Ultrafine Monitors

Model	Description
27BP85UN-W	27" LG MONITOR, 3840x2160, 16:9 IPS, USB-C, HDMI 2.0 (2), DISPLAY PORT, USB 3.0 (2 DOWN)
27BP450Y-I	27" LG MONITOR, 1920X1080, 16:9 IPS, HDMI, DP
27CN650I-6N **NEW**	27" LG THIN CLIENT IGEL PRE-INSTALLED AIO MONITOR, 1920X1080, INTEL CELERON QUAD CORE, 4GB DDR, 16GB eMMC, IPS, TAA, HW TPM

Starin is your Supply Partner. To place you order, please go to www.starin.biz or email your PO to orders@starin.biz

Starin | 136 Venturi Drive | Chesterton, IN 46304 | P 219-929-4127 | F 219-929-4377 | W: www.starin.biz